

---

# ATS-4015T

---

## TEMPEST Laser Printer

### SDIP 27 Level B



The ATS-4015T is the Tempest version of the HP LaserJet 4015 Printer series. It supports up to 1200 dpi resolution at full engine speed of 50 pages per minute.

Our design provides all of the OEM functionality while allowing easy access for maintenance.

#### Key Features:

- Print speed up to 50 ppm
- 128 MB RAM (max 640 MB)
- 540 MHz processor
- HP Jetdirect Gigabit Ethernet embedded print server with IPsec
- Standard input capacity of 600-sheets with 1x 100 sheet tray and 1x 500-sheet input tray
- Expandable to 3600 pages with optional 3x 500-sheet input trays and a 1.500-sheet high capacity input tray
- Recommended monthly print volume 3.000 to 15.000 pages
- Duty cycle up to 225.000 pages
- SDIP 27 Level B

Preliminary specifications, subject to change without notice!  
Released August 2009



**CordSen Engineering GmbH**  
Am Klinggraben 1 • D-63500 Seligenstadt  
TEMPEST • RUGGED • MIL-SPEC

Tel.: +49 (0)6182 / 92 94 0  
Fax: +49 (0)6182 / 92 94 45  
<http://www.cordsen.com>

---

# ATS-4015T

---

## Technical Data

### Interfaces

- High-Speed USB
- Ethernet 100Base-FX

### Printing Performance

- Print resolution up to 1200 x 1200 dpi
- Print speed (max) 50 pages per minute
- First page out black: < 8,5 sec (from ready mode)
- Up to 225.000 pages per month

### Processor

- 540 MHz, Motorola ColdFire® V5e

### Print quality

- HP REt, HP Fast Res 1200, HP ProRes 1200, HP 600dpi, HP 300 dpi

### Memory

- 128 MB, expandable to 640 MB through One 144-pin DDR2 DIMM slot

### Printer Languages

- HP PCL 6, HP PCL 5e, HP Postscript Level 3 Emulation, direct PDF (v 1.4) Media Types

### Paper Handling

- Capacity tray 1:  
Sheets..... 100  
Envelopes..... 10
- Capacity tray 2:  
Sheets..... 500
- Capacity tray 3 (optional):  
Sheets..... 500
- Output:  
Sheets: ..... Up to 600  
Envelopes: ..... Up to 10  
Transparencies: ..... Up to 600
- Type: Paper (bond, colour, letterhead, plain, preprinted, prepunched, recycled, rough, light), envelopes, labels, cardstock, transparencies

### Temperature for printer and toner:

- Operating: 15° to 32,5° C; Storage: 0° to 35° C

### Humidity:

- Operating: 10% to 80% RH; Storage: 10% to 95% RH

### Power Requirements, Power Consumptions

- Input voltage:  
110 to 127 VAC (± 10 percent), 50/60 Hz (± 2 Hz),  
220 to 240 VAC (± 10 percent), 50/60 Hz (± 2 Hz)
- Power consumption:  
Printing: ..... 840 watts  
Ready: ..... 18 watts  
Sleep: ..... 12 watts  
Off: ..... 0.4 watts

### Compatible Operating Systems

- Microsoft® Windows® 2000, XP Home; XP Professional; Server 2003; Certified for Windows Vista

### Typefaces/fonts

- 80 HP Font set (plus Greek, Hebrew, Cyrillic, Arabic)

### Warranty

- A one year return to factory warranty is standard on CE products

### Dimensions (W x D x H)

- Base model: 419 x 450 x 393 mm
- HP P4015tn: 419 x 450 x 546 mm

### Weight

- Base model: 26,5 kg
- HP P4015tn: 35,5 kg

Preliminary specifications, subject to change without notice!  
Released August 2009



**CordSen Engineering GmbH**  
Am Klinggraben 1 • D-63500 Seligenstadt  
TEMPEST • RUGGED • MIL-SPEC

**Tel.: +49 (0)6182 / 92 94 0**  
**Fax: +49 (0)6182 / 92 94 45**  
**<http://www.cordsen.com>**